Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Toe rail pad eye - Asymetric - Dia: 9 - 13 mm

Part #16614





Description

asymetric model allowing to use the toe rail for attachment (blocks, barber hauler, boom brake...)
It prevents from damaging the toe rail
Easy installation by unscrewing the pin
For asymetric toe rail

Applications

Allows to attach blocks, barber hauler, boom brake or boom preventer...

Technical information

	Materials	HR 17.4 PH stainless steel grade
⛵	Working load (kg)	960
	Breaking load (kg)	3000
	Weight (g)	186
	A (mm)	De 9 à 13
	C (mm)	De 2 à 5
	D (mm)	14
	H (mm)	40

Caption

⛵ Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026