Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Softlink 4.0 - Soft shackle - Dia 4 mm - Length: 80 mm

Part #21224



Description

SoftLink is a soft shackle developed by Wichard for recreational sailors looking for performance and ease of use.
For the same strength, SoftLink is 4 or 5 times lighter than a 316L stainless steel shackle.
No knowledge of ropework required
Replaces shackles and snap hooks
Easy to fit and easy to open
Remarkably light and strong
Re-usable
4 sizes available
Materials: stainless steel and Dyneema SK 78
Loop diameter: 4 mm
Loop length: 80 mm

Applications

Fastenings
Replaces shackles and snap hooks

Technical information

Materials	316L stainless steel grade - Dyneema SK78
Loop diameter (mm)	4
Loop length (mm)	80
Breaking load (kg)	3000
Weight (g)	23

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026