
Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

FRXP22 - Friction ring - Dia 22 mm - Large opening

Part #22202





Description

Wichard expands its existing range of friction rings with four new large-opening models. These new additions deliver the same premium finish, thanks to their high-quality anodized treatment and a carefully engineered design that prevents premature rope wear.
The large-passage models can accommodate multiple lines and are particularly well-suited for 3D sail trimming systems. The outer groove can also take a line or a bungee cord to keep the ring securely in position.

Applications

- 3D sail trimming
- Various applications requiring multiple line

Technical information

Materials	Hard anodized aluminium
Colour	Black
Working load (kg)	1000
Weight (g)	34
B (mm)	22
C (mm)	14
D (mm)	2.5
D diameter (mm)	44

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026