Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Stainless steel single block - sheave 25 - For 25 mm stanchion

Part #30025



Description

Complete range of stainless steel blocks for dinghies
Lightweight, reliable and good performance
Available in a wide range of size and fastening systems

Applications

For stanchion applications: furling system line

Technical information

Materials	Composite sheave 316L stainless steel grade cheeks
Rope size	Pour cordage de 8 à 10 mm
Length (mm)	65
Width (mm)	53
Thickness (mm)	21
Sheave diameter (mm)	25
Working load (kg)	280
Breaking load (kg)	400
Weight (g)	490

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026