Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Double plain bearing block - Sheave 35 - Swivel head & becket

Part #62206



Description

> Complete range of plain bearing blocks > Modern design > Withstand high loads > Ideal for static operations > The sheave runs on the stainless steel bush > Light cheeks protecting the sheave > Wide choice of fastenings thanks to the universal head >

Applications

> Mainsheet systems > Halyard applications > boom vangs > spinnaker control lines on dinghies, catamaran and small keelboats

Technical information

Materials	Grade 316L stainless steel head configuration Grade 316L stainless steel load straps POM cheeks Composite saddle for cam models Composite sheave Terminal (shackle i.e...): 316L stainless steel grade
Rope size	Pour cordage de 8 à 9 mm
Length (mm)	101
Width (mm)	37
Thickness (mm)	40
Sheave diameter (mm)	35
Schackle diameter (mm)	5
Working load (kg)	480
Breaking load (kg)	900
Weight (g)	128

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026