Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Single plain bearing block - Sheave 70 - Cheek block - M8

Part #65120





Description

Complete range of plain bearing blocks
Modern design
Withstand high loads
Ideal for static operations
The sheave runs on the stainless steel bush
Light cheeks protecting the sheave
Wide choice of fastenings thanks to the universal head

Applications

Cheek block applications for genoa sheet

Technical information

Materials	Grade 316L stainless steel head configuration Grade 316L stainless steel load straps POM cheeks Composite saddle for cam models Composite sheave Terminal (shackle i.e...): 316L stainless steel grade
Rope size	Pour cordage de 14 mm
Length (mm)	103
Width (mm)	80
Thickness (mm)	34
Sheave diameter (mm)	70
Working load (kg)	1200
Breaking load (kg)	2700
Weight (g)	294

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026