
Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

U-bolt pad eye - Dia: 12 mm - Length: 130 mm

Part #6526





Description

Fully dropforged product with high quality stainless steel
Outstanding working and breaking loads
For any kind of fastening applications (shrouds, lilfelines, blocks...)
Delivered with bolts and counterplate
Max tightening torque: 60 Nm

Applications

Various fastening applications: shrouds, lifelines, blocks...

Technical information

Materials	316L stainless steel grade
Length (mm)	130
Working load (kg)	6400
Breaking load (kg)	10000
Weight (g)	349
A (mm)	44
B (mm)	34
C (mm)	70
D diameter (mm)	12
L (mm)	130

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026