Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

# Fiddle plain bearing block - Sheave 70 - Swivel head becket & cam

Part #65408



## Description

Complete range of plain bearing blocks
Modern design
Withstand high loads
Ideal for static operations
The sheave runs on the stainless steel bush
Light cheeks protecting the sheave
Wide choice of fastenings thanks to the universal head

## Applications

Mainsheet systems
Halyard applications
boom vangs
Downhaul
Mast head block

## Technical information

| | |
|---|---|
| Materials | Grade 316L stainless steel head configuration<br>Grade 316L stainless steel load straps<br>POM cheeks<br>Composite saddle for cam models<br>Composite sheave<br>Terminal (shackle i.e...): 316L stainless steel grade |
| Rope size | Pour cordage de 14 mm |
| Length (mm) | 236 |
| Width (mm) | 120 |
| Thickness (mm) | 80 |
| Sheave diameter (mm) | 70 |
| Schackle diameter (mm) | 8 |
| Working load (kg) | 480 |
| Breaking load (kg) | 2700 |
| Weight (g) | 748 |

### Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026