Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

# D ring - 316L - Stock dia: 6 mm - Inner dia: 50 mm

Part #6712







## Description

Forged D rings (grade 316L stainless steel)
Increased working load limits
Stock diameter: 6 mm
Inside dimensions: 50 mm

## Applications

Webbing applications

## Technical information

| | |
|---|---|
| Materials | 316L stainless steel grade |
| Breaking load (kg) | 3000 |
| Weight (g) | 35 |
| A (mm) | 6 |
| C (mm) | 50.2 |
| D (mm) | 26.4 |
| E (mm) | 38.5 |
| F (mm) | 62.2 |

### Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026