Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Double ball bearing block - Sheave 18 - Fixed eye

Part #70213



Description

Complete range of ball bearing blocks
Modern design
Innovative design with two lateral races of ball bearings
Smooth running for low load adnhigh speed action
Under high load the hub runs on stainless steel bush which allows the sheave to run freely
Light cheeks protecting the sheave
Wide choice of fastenings thanks to the universal head
The sheave can be removed for maintenance

Applications

For dinghies and catamarans applications: genoa sheets, boom vang, footmast block, masthead block...
For larger yachts: barber-hauler, various, control lines...

Technical information

Materials	Grade 316L stainless steel head Delrin® ball bearings configuration Grade 316L stainless steel load straps Polycarbonate cheeks Composite sheave
Rope size	Pour cordage de 4 à 6 mm
Length (mm)	45
Width (mm)	18
Thickness (mm)	28
Sheave diameter (mm)	18
Working load (kg)	320
Breaking load (kg)	700
Weight (g)	41

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026