Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

# Proline - Elastic webbing 1.4M - 1 hook - Overload indicator

Part #7038





## Description

Tether with 1 double action safety hook - Elastic webbing - 1.40 m
New design, new automatic closing and opening mechanism. The new Proline generation has been designed to offer you the highest level of safety at sea.

Double safety hook :
New automatic closing and opening mechanism
Wide opening : 26 mm
V-Nose feature (patented) : easy hooking and unhooking

High quality elastic webbing :
Retro-reflective and visible at night
Compact and light

Exclusive feature: SmartLoop
Product can adapt to suit all needs and users.
SmartLoop lets you:
turn a single webbing tether into a double webbing tether
turn a double webbing tether into two single webbing tethers

Material :
Anodised aluminium hook offering light weight and mechanical and corrosion resistance.

Regulations :
Compliance with ISO 12401:2009 and WORLD SAILING regulations (OSR)
Overload indicator on all models

## Applications

Safety on board

## Technical information

| | |
|---|---|
| Materials | Aluminium snap hook with hard anodization - Polyamide webbing |
| Weight (g) | 190 |

### Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026