Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Single roller block - Sheave 50 - Swivel head & becket

Part #94106



Description

Complete range of blocks
Excellent high-speed low load and high-function load characteristics
Interchangeable head fastening systems for multiple attachment methods
Protection of the sheave by the cheeks for added durability
Multiple position, grub screw lockable head post swivel
Alloy sheaves design to suit modern ropes

Applications

Genoa and spinnaker sheets
Mainsail systems and travelers
Running backstays

Technical information

Materials	Delrin® roller bearing Forged stainless steel shackle Stainless steel swivel head Hard anodized aluminium sheave Aluminium cheeks (hard coat anodization)
Rope size	Pour cordage de 8 à 10 mm
Length (mm)	113
Width (mm)	52
Thickness (mm)	28
Sheave diameter (mm)	50
Schackle diameter (mm)	6
Working load (kg)	480
Breaking load (kg)	1500
Weight (g)	124

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026